

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 10/12/2015 Date of issue: 10/12/2015

Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: ONE STEP FIBERGLASS CLEANER & WAX WITH PTEF

Product Code: BP56637, BPC56637, BP56644

Intended Use of the Product
Use of the Substance/Mixture: Polish.

Name, Address, and Telephone of the Responsible Party

Company Bass Pro Shops 2500 E. Kearney Springfield, MO 65898 (800)227-7776

www.basspro.com

Emergency Telephone Number

Emergency Number: US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Flam. Liq. 3 H226 Skin Irrit. 2 H315 STOT SE 3 H336

Full text of H-phrases: see section 16

Label Elements GHS-US Labeling

Hazard Pictograms (GHS-US)





Signal Word (GHS-US) : Warning

Hazard Statements (GHS-US) : H226 - Flammable liquid and vapor.

H315 - Causes skin irritation.

H336 - May cause drowsiness or dizziness.

Precautionary Statements (GHS-US): P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical, lighting, ventilating equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear eye protection, protective gloves, protective clothing.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position

comfortable for breathing.

P312 - Call a poison center or doctor if you feel unwell.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

10/12/2015 MTMOFM-CC EN (English US) 1/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P362 - Take off contaminated clothing and wash before reuse.

P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂) to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P235 - Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Aquatic Acute 3

Aquatic Chronic 3

H402 - Harmful to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

P273 - Avoid release to the environment.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Kerosine, petroleum	(CAS No) 8008-20-6	10 - 30*	Flam. Liq. 3, H226
			Skin Irrit. 2, H315
			STOT SE 3, H336
			Asp. Tox. 1, H304
			Aquatic Chronic 2, H411
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	5 – 10*	Skin Irrit. 2, H315
			STOT SE 3, H336
			Asp. Tox. 1, H304
			Aquatic Acute 2, H401
			Aquatic Chronic 2, H411
Diatomaceous earth	(CAS No) 61790-53-2	5 – 10*	Not classified
Methyl alcohol	(CAS No) 67-56-1	< 0.1	Flam. Liq. 2, H225
			Acute Tox. 3 (Oral), H301
			Acute Tox. 3 (Dermal), H311
			Acute Tox. 3 (Inhalation:vapour), H331
			STOT SE 1, H370
Diethanolamine	(CAS No) 111-42-2	< 0.1	Acute Tox. 4 (Oral), H302
			Skin Irrit. 2, H315
			Eye Dam. 1, H318
			Carc. 2, H351
			STOT RE 2, H373
			Aquatic Acute 2, H401
			Aquatic Chronic 3, H412

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

10/12/2015 MTMOFM-CC EN (English US) 2/15

^{*} A range of concentration as prescribed by Controlled Products Regulations has been used where necessary, due to varying composition. The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]. In the event of an emergency, chemical identities and exact percentages of the proprietary ingredients may need to be disclosed to emergency personnel upon request.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye irritation. Vapors may cause drowsiness and dizziness.

Inhalation: May cause drowsiness or dizziness.

Skin Contact: Causes skin irritation. **Eye Contact:** May cause eye irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated or prolonged skin contact may cause dermatitis and defatting. **Indication of Any Immediate Medical Attention and Special Treatment Needed**

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable/explosive vapor-air mixture.

Reactivity: Reacts with (strong) oxidizers: (increased) risk of fire.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Silicon oxides. Nitrogen compounds. Sulfur compounds. Iodine vapour.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat, sparks, open flames, hot surfaces. – No smoking. Avoid all contact with skin, eyes, or clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Use only non-sparking tools.

Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

10/12/2015 MTMOFM-CC EN (English US) 3/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Precautions for Safe Handling: Take precautionary measures against static discharge. Use only non-sparking tools. Keep away from heat, sparks, open flames, hot surfaces. – No smoking.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations. **Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. **Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s)

Polish.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Diatomaceous earth (61790	-53-2)	
Mexico	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
British Columbia	OELTWA (mg/m³)	4 mg/m³ (total dust)
		1.5 mg/m³ (respirable dust)
New Brunswick	OELTWA (mg/m³)	3 mg/m³ (particulate matter containing no Asbestos and
		<1% Crystalline silica, respirable fraction)
		10 mg/m³ (particulate matter containing no Asbestos and
		<1% Crystalline silica, inhalable fraction)
Ontario	OELTWA (mg/m³)	10 mg/m³ (containing no Asbestos and <1% Crystalline
		silica-inhalable)
		3 mg/m³ (containing no Asbestos and <1% Crystalline
		silica-respirable)
Québec	VEMP (mg/m³)	6 mg/m³ (containing no Asbestos and <1% Crystalline
		silica-total dust)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)
		6 mg/m³ (respirable fraction)
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
		3 mg/m³ (respirable fraction)
Kerosine, petroleum (8008-2		
USA ACGIH	ACGIH TWA (mg/m³)	200 mg/m³ (application restricted to conditions in which
		there are negligible aerosol exposures-total hydrocarbon
		vapor)
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure
		by the cutaneous route, Confirmed Animal Carcinogen with
		Unknown Relevance to Humans
USA NIOSH	NIOSH REL (TWA) (mg/m³)	100 mg/m ³
Alberta	OEL TWA (mg/m³)	200 mg/m ³
British Columbia	OELTWA (mg/m³)	200 mg/m³ (application restricted to conditions in which
		there are negligible aerosol exposures)
Manitoba	OELTWA (mg/m³)	200 mg/m³ (application restricted to conditions in which
		there are negligible aerosol exposures-total Hydrocarbon
		vapor)
Newfoundland & Labrador	OEL TWA (mg/m³)	200 mg/m³ (application restricted to conditions in which
		there are negligible aerosol exposures-total Hydrocarbon
		vapor)
Nova Scotia	OELTWA (mg/m³)	200 mg/m³ (application restricted to conditions in which
		there are negligible aerosol exposures-total Hydrocarbon

10/12/2015 MTMOFM-CC EN (English US) 4/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Treestand To Tederal Register / You /	7, No. 58 / Monday, March 26, 2012 / Rules And Reg	
		vapor)
Ontario	OEL TWA (mg/m³)	200 mg/m³ (restricted to conditions where there is
		negligible aerosol exposure)
Prince Edward Island	OEL TWA (mg/m³)	200 mg/m³ (application restricted to conditions in which
		there are negligible aerosol exposures-total Hydrocarbon
		vapor)
Saskatchewan	OEL STEL (mg/m³)	250 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	200 mg/m ³
Methyl alcohol (67-56-1)		
Mexico	OEL TWA (mg/m³)	260 mg/m ³
Mexico	OELTWA (ppm)	200 ppm
Mexico	OEL STEL (mg/m³)	310 mg/m ³
Mexico	OEL STEL (ppm)	250 ppm
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure
		by the cutaneous route
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m³)	325 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
USA IDLH	US IDLH (ppm)	6000 ppm
Alberta	OEL STEL (mg/m³)	328 mg/m ³
Alberta	OEL STEL (ppm)	250 ppm
Alberta	OEL TWA (mg/m³)	262 mg/m ³
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	250 ppm
British Columbia	OELTWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	250 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m³)	328 mg/m ³
New Brunswick	OEL STEL (ppm)	250 ppm
New Brunswick	OELTWA (mg/m³)	262 mg/m³
New Brunswick	OEL TWA (ppm)	200 ppm
Newfoundland & Labrador	OEL STEL (ppm)	250 ppm
Newfoundland & Labrador	OELTWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	250 ppm
Nova Scotia	OELTWA (ppm)	200 ppm
Nunavut	OEL STEL (mg/m³)	328 mg/m ³
Nunavut	OEL STEL (ppm)	250 ppm
Nunavut	OELTWA (mg/m³)	262 mg/m ³
Nunavut	OELTWA (ppm)	200 ppm
Northwest Territories	OEL STEL (mg/m³)	328 mg/m ³
Northwest Territories	OEL STEL (ppm)	250 ppm
Northwest Territories	OELTWA (mg/m³)	262 mg/m ³
Northwest Territories	OELTWA (ppm)	200 ppm
Ontario	OEL STEL (ppm)	250 ppm
Ontario	OELTWA (ppm)	200 ppm
Prince Edward Island	OEL TWA (ppm)	250 ppm
LING LAWAIU DAIIU	OPPOITE (hhm)	MAA hhiii

10/12/2015 MTMOFM-CC EN (English US) 5/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

	·		
Prince Edward Island	OELTWA (ppm)	200 ppm	
Québec	VECD (mg/m³)	328 mg/m³	
Québec	VECD (ppm)	250 ppm	
Québec	VEMP (mg/m³)	262 mg/m³	
Québec	VEMP (ppm)	200 ppm	
Saskatchewan	OEL STEL (ppm)	250 ppm	
Saskatchewan	OELTWA (ppm)	200 ppm	
Yukon	OEL STEL (mg/m³)	310 mg/m ³	
Yukon	OEL STEL (ppm)	250 ppm	
Yukon	OELTWA (mg/m³)	260 mg/m³	
Yukon	OELTWA (ppm)	200 ppm	
Diethanolamine (111-42-2)			
USA ACGIH	ACGIH TWA (mg/m³)	1 mg/m³ (inhalable fraction and vapor)	
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure	
		by the cutaneous route, Confirmed Animal Carcinogen with	
		Unknown Relevance to Humans	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	15 mg/m ³	
USA NIOSH	NIOSH REL (TWA) (ppm)	3 ррт	
Alberta	OELTWA (mg/m³)	2 mg/m³	
British Columbia	OEL TWA (mg/m³)	2 mg/m³	
Manitoba	OEL TWA (mg/m³)	1 mg/m³ (inhalable fraction and vapor)	
New Brunswick	OEL TWA (mg/m³)	2 mg/m³	
New Brunswick	OELTWA (ppm)	0.46 ppm	
Newfoundland & Labrador	OEL TWA (mg/m³)	1 mg/m³ (inhalable fraction and vapor)	
Nova Scotia	OEL TWA (mg/m³)	1 mg/m³ (inhalable fraction and vapor)	
Nunavut	OEL STEL (mg/m³)	26 mg/m ³	
Nunavut	OEL STEL (ppm)	6 ppm	
Nunavut	OEL TWA (mg/m³)	13 mg/m ³	
Nunavut	OEL TWA (ppm)	3 ррт	
Northwest Territories	OEL STEL (mg/m³)	26 mg/m ³	
Northwest Territories	OEL STEL (ppm)	6 ppm	
Northwest Territories	OEL TWA (mg/m³)	13 mg/m^3	
Northwest Territories	OEL TWA (ppm)	3 ррт	
Ontario	OELTWA (mg/m³)	1 mg/m³ (inhalable fraction and vapor)	
Prince Edward Island	OEL TWA (mg/m³)	1 mg/m³ (inhalable fraction and vapor)	
Québec	VEMP (mg/m³)	13 mg/m ³	
Québec	VEMP (ppm)	3 ррт	
Saskatchewan	OEL STEL (mg/m³)	4 mg/m³	
Saskatchewan	OEL TWA (mg/m³)	2 mg/m³	
Petroleum distillates, hydro	Petroleum distillates, hydrotreated light (64742-47-8)		
British Columbia	OEL TWA (mg/m³)	200 mg/m³ (application restricted to conditions in which	
		there are negligible aerosol exposures)	
•	-		

Exposure Controls

Appropriate Engineering Controls: Ensure all national/local regulations are observed. Use explosion-proof equipment. Take precautionary measures against static discharges. Gas detectors should be used when flammable gases/vapors may be released. **Personal Protective Equipment:** Insufficient ventilation: wear respiratory protection. Safety glasses. Gloves. Protective clothing.









Materials for Protective Clothing: Wear fire/flame resistant/retardant clothing.

10/12/2015 MTMOFM-CC EN (English US) 6/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses. **Skin and Body Protection:** Wear fireproof clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Liquid Appearance : Cream

Odor: CharacteristicOdor Threshold: Not available

pH : 7

Evaporation Rate: Not availableMelting Point: 0 °C (32 °F) (32 °F)Freezing Point: Not availableBoiling Point: Not available

Flash Point : 59 °C (138.2 °F). Does not sustain combustion according to the Sustained

Combustibility Test prescribed in part III, 32.5.2 of the *United Nations*

Manual of Tests and Criteria.

Auto-ignition Temperature Not available Not available **Decomposition Temperature** Flammability (solid, gas) Not available **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available **Vapor Pressure** Not available Relative Vapor Density at 20 °C Not available **Relative Density** 1.012 (water = 1)

Specific Gravity : 1.012

Solubility : Soluble in water.

Partition Coefficient: N-Octanol/Water : Not available

Viscosity : Not available

Explosion Data – Sensitivity to Mechanical Impact: Not expected to present an explosion hazard due to mechanical impact. **Explosion Data – Sensitivity to Static Discharge**: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts with (strong) oxidizers: (increased) risk of fire.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Silicon oxides. Nitrogen compounds. Sulfur compounds. Iodine

vapour.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified **ID50 and IC50 Data:** Not available

Skin Corrosion/Irritation: Causes skin irritation.

pH: 7

Serious Eve Damage/Irritation: Not classified

pH: 7

10/12/2015 MTMOFM-CC EN (English US) 7/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available **Carcinogenicity:** Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause drowsiness or dizziness.

Symptoms/Injuries After Skin Contact: Causes skin irritation.

Symptoms/Injuries After Eye Contact: May cause eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects. **Chronic Symptoms:** Repeated or prolonged skin contact may cause dermatitis and defatting.

Information on Toxicological Effects - Ingredient(s)

ID50 and IC50 Data:

Kerosine, petroleum (8008-20-6)		
ID50 Oral Rat	> 5000 mg/kg	
ID50 Dermal Rabbit	> 2000 mg/kg	
IC50 Inhalation Rat	> 5.28 mg/l/4h	
Methyl alcohol (67-56-1)		
IC50 Inhalation Rat	22500 ppm (Exposure time: 8 h)	
ATE US (oral)	100.00 mg/kg body weight	
ATE US (dermal)	300.00 mg/kg body weight	
ATE US (vapors)	3.00 mg/l/4h	
Diethanolamine (111-42-2)		
ID50 Oral Rat	1820 mg/kg	
Petroleum distillates, hydrotreated light (64742-47-8)		
ID50 Oral Rat	> 5000 mg/kg	
ID50 Dermal Rabbit	> 2000 mg/kg	
LC50 Inhalation Rat	> 5.2 mg/l/4h	
Diatomaceous earth (61790-53-2)		
IARC Group	3	
Diethanolamine (111-42-2)		
IARC Group	2B	
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.	
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.	

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - **General:** Harmful to aquatic life with long lasting effects.

Kerosine, petroleum (8008-20-6)		
IC50 Fish 1	2 - 5 mg/kg (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])	
NOEC chronic fish	0.098 mg/l (PETROTOX, Klimmish score: 2)	
Methyl alcohol (67-56-1)		
IC50 Fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
IC 50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
Diethanolamine (111-42-2)		
IC50 Fish 1	4460 (4460 - 4980) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-	
	through])	
EC50 Daphnia 1	55 mg/l (Exposure time: 48 h - Species: Daphnia magna)	

10/12/2015 MTMOFM-CC EN (English US) 8/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

IC 50 Fish 2	1200 (1200 - 1580) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Other Aquatic Organisms 2	2.1 (2.1 - 2.3) mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)	
ErC50 (algae)	2.2 mg/l (Exposure time: 96 h - Species: Pseudokirchnerella subcapitata [Static])	
Petroleum distillates, hydrotreated light (64742-47-8)		
IC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
IC 50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	

Persistence and Degradability

ONE STEP FIBERGIASS CLEANER & WAX WITH PTEF	
Persistence and Degradability	Not established.

Bioaccumulative Potential

ONE STEP FIBERGIASS CLEANER & WAX WITH PTEF		
Bioaccumulative Potential	Not established.	
Methyl alcohol (67-56-1)		
BCF Fish 1	< 10	
Log Pow	-0.77	
Diethanolamine (111-42-2)		
BCF Fish 1	(no significant bioconcentration)	
Log Pow	-2.18 (at 25 °C)	
Petroleum distillates, hydrotreated light (64742-47-8)		
BCF Fish 1	61 - 159	

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG/IMDG

UN Number Not regulated for transport

UN Proper Shipping Name Transport Hazard Class(es)Not regulated for transport

Transport by sea Not regulated for transport

In Accordance With IMDG Not regulated for transport

In Accordance With IATA/ICAO Not regulated for transport

In Accordance With TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

ONE STEP FIBERGIASS CLEANER & WAX WITH PTEF		
SARA Section 311/312 Hazard Classes	Fire hazard	
	Immediate (acute) health hazard	
Diatomaceous earth (61790-53-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Kerosine, petroleum (8008-20-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Methyl alcohol (67-56-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Listed on United States SARA Section 313		

10/12/2015 MTMOFM-CC EN (English US) 9/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard	
	Immediate (acute) health hazard	
	Fire hazard	
SARA Section 313 - Emission Reporting	1.0 %	
Diethanolamine (111-42-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Listed on United States SARA Section 313		
SARA Section 313 - Emission Reporting	1.0 %	
Petroleum distillates, hydrotreated light (64742-47-8)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes	Fire hazard	
	Immediate (acute) health hazard	

US State Regulations

Methyl alcohol (67-56-1)	
U.S California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of
	California to cause birth defects.
Diethanolamine (111-42-2)	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of
_	California to cause cancer.

Diatomaceous earth (61790-53-2)

- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits Mineral Dusts
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits TWAs
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- **U.S. New York Occupational Exposure Limits Mineral Dusts**
- U.S. New York Occupational Exposure Limits TWAs
- U.S. Oregon Permissible Exposure Limits Mineral Dusts
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs

Kerosine, petroleum (8008-20-6)

- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- RTK U.S. Massachusetts Right To Know List
- U.S. Minnesota Chemicals of High Concern
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AAIs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. California Safer Consumer Products Initial List of Candidate Chemicals and Chemical Groups

10/12/2015 MTMOFM-CC EN (English US) 10/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Methyl alcohol (67-56-1)

- U.S. California Proposition 65 Maximum Allowable Dose Levels (MADL)
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Colorado Hazardous Wastes Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- **U.S. Connecticut Volatile Substances**
- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- **U.S.** Illinois Toxic Air Contaminants
- U.S. Louisiana Reportable Quantity List for Pollutants
- U.S. Maine Air Pollutants Hazardous Air Pollutants
- U.S. Maine Chemicals of High Concern
- U.S. Massachusetts Allowable Ambient Limits (AALs)
- **U.S. Massachusetts Allowable Threshold Concentrations (ATCs)**
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- RTK U.S. Massachusetts Right To Know List
- U.S. Massachusetts Threshold Effects Exposure Limits (TELs)
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits Skin Designations
- U.S. Michigan Occupational Exposure Limits STELs
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Michigan Polluting Materials List
- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Groundwater Health Risk Limits
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits Skin Designations
- U.S. Minnesota Permissible Exposure Limits STELs
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AAIs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New Jersey Water Quality Ground Water Quality Criteria
- U.S. New Jersey Water Quality Practical Quantitation Levels (PQLs)
- U.S. New York Occupational Exposure Limits Skin Designations
- U.S. New York Occupational Exposure Limits TWAs
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour

10/12/2015 MTMOFM-CC EN (English US) 11/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

- U.S. North Dakota Hazardous Wastes Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. California Safer Consumer Products Initial List of Candidate Chemicals and Chemical Groups
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels 1-Hour
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels Annual
- U.S. South Carolina Toxic Air Pollutants Maximum Allowable Concentrations
- U.S. South Carolina Toxic Air Pollutants Pollutant Categories
- U.S. Tennessee Occupational Exposure Limits Skin Designations
- U.S. Tennessee Occupational Exposure Limits STELs
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits Skin Designations
- U.S. Vermont Permissible Exposure Limits STELs
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Dangerous Waste Discarded Chemical Products List
- U.S. Washington Permissible Exposure Limits Skin Designations
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs

Diethanolamine (111-42-2)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Illinois Toxic Air Contaminant Carcinogens
- **U.S.** Illinois Toxic Air Contaminants
- U.S. Louisiana Reportable Quantity List for Pollutants
- U.S. Maine Air Pollutants Hazardous Air Pollutants
- RTK U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Michigan Polluting Materials List
- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. California Safer Consumer Products Initial List of Candidate Chemicals and Chemical Groups
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels Annual

10/12/2015 MTMOFM-CC EN (English US) 12/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

- U.S. South Carolina Toxic Air Pollutants Maximum Allowable Concentrations
- U.S. South Carolina Toxic Air Pollutants Pollutant Categories
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

Petroleum distillates, hydrotreated light (64742-47-8)

- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Canadian Regulations

Canadian regulations	
ONE STEP FIBERGIASS CLEAN	ER & WAX WITH PTEF
WHMIS Classification	Class B Division 3 - Combustible Liquid
	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Diatomaceous earth (61790-53-2)				
isted on the Canadian NDSL (Non-Domestic Substances List)				
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects			
Kerosine, petroleum (8008-2	Kerosine, petroleum (8008-20-6)			
Listed on the Canadian DSL (D	n the Canadian DSL (Domestic Substances List)			
WHMIS Classification	Class B Division 3 - Combustible Liquid			
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects			
Methyl alcohol (67-56-1)	Methyl alcohol (67-56-1)			
Listed on the Canadian DSL (D	isted on the Canadian DSL (Domestic Substances List)			
Listed on the Canadian IDL (In	d on the Canadian IDL (Ingredient Disclosure List)			
IDL Concentration 1 %	DL Concentration 1 %			
WHMIS Classification	Class B Division 2 - Flammable Liquid			
	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects			
	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects			
Diethanolamine (111-42-2)				
Listed on the Canadian DSL (D	omestic Substances List)			
Listed on the Canadian IDL (In	gredient Disclosure List)			
IDL Concentration 1 %				
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects			
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects			
Petroleum distillates, hydrot	reated light (64742-47-8)			
Listed on the Canadian DSL (Domestic Substances List)				
WHMIS Classification	Class B Division 3 - Combustible Liquid			
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects			

10/12/2015 MTMOFM-CC EN (English US) 13/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 10/12/2015

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

run text Phrases:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
Н317	May cause an allergic skin reaction
H318	Causes serious eye damage
Н319	Causes serious eye irritation
Н331	Toxic if inhaled
H332	Harmful if inhaled
Н335	May cause respiratory irritation
Н336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
Н370	Causes damage to organs
Н373	May cause damage to organs through prolonged or repeated exposure

10/12/2015 MTMOFM-CC EN (English US) 14/15

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard : 1 - Exposure could cause irritation but only minor residual


injury even if no treatment is given.

NFPA Fire Hazard : 2 - Must be moderately heated or exposed to relatively

high temperature before ignition can occur.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



Party Responsible for the Preparation of This Document

Bass Pro Shops

Phone Number: (800)227-7776

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2

10/12/2015 MTMOFM-CC EN (English US) 15/15